

# nifty

## TrackDrive

### TRACK MOUNTED WORK PLATFORM

**25ft, 34ft & 50ft**  
Platform heights

### Superb Gradeability

Will climb very steep  
inclines as high as 60% (31°)

### Excellent Traction

Better grip on uneven terrain

### Fully Proportional Hydraulic Controls

Simple, reliable &  
easy to maintain

### Weight Saving Design

Lower cost transportation &  
better fuel economy on site

### Non-Marking Tracks

Optional rubber-free tracks  
available for indoor usage

### Variable Width Tracks

Access to narrow openings  
improving versatility



**niftylift.com**



# nifty TrackDrive

Nifty's new TrackDrive platforms offer a range of capabilities to suit operator requirements. The TD24 is a compact and maneuverable machine capable of passing through a 2ft 6in opening making it the ideal tool for jobs where space is limited. The TD34T is available in two versions, the standard and narrow width machines. With 60° gradeability both offer excellent traction on steep or rough terrain and the narrow version will pass through a 0.75m opening for restricted access applications. The TD50 provides an impressive working envelope and its TrackDrive base allows it to travel over ground where even a 4WD SP platform would have difficulty finding traction.



Weight saving designs mean that site-to-site transportation is more economical. The platforms are also more efficient, allowing them to work for longer while using less fuel.



Also available are rubber-free urethane tracks. Ideal for internal or clean applications, maximizing the TrackDrive's utilization

SPECIFICATIONS	TD24	TD34TN	TD34T	TD50
<b>Height - Working</b>	30ft 10in	40ft	40ft	56ft 1in
<b>Height - Platform</b>	25ft 3in	33ft 6in	33ft 6in	49ft 6in
<b>Outreach - Working</b>	11ft 6in	20ft 1in	20ft 1in	28ft 6in
<b>Slew</b>	355°	406°	406°	355°
<b>Width - Traveling</b>	2ft 6in	2ft 6in - 3ft 8in	3ft 6in	6ft 8in
<b>Width - Working</b>	6ft 11in	9ft 7in	11ft 8in	14ft 4in
<b>Height - Stowed</b>	6ft 3in	6ft 3in	6ft 3in	6ft 10in
<b>Length</b>	12ft	12ft 11in	12ft 11in	18ft 4in
<b>Weight</b>	1,870lbs*	3,894lbs*	3,960lbs*	6,380lbs*
<b>Platform Capacity</b>	265lbs	265lbs	500lbs	500lbs
<b>Platform Size</b>	2ft x 2ft	2ft 5in x 2ft	3ft 8in x 2ft 1in	3ft 8in x 2ft 1in
<b>Drive Speed</b>	1.3 - 2.1mph	0.6 - 1.0mph	0.6 - 1.0mph	0.6 - 1.0mph
<b>Gradeability</b>	30%	60%	60%	32%
<b>Control System</b>	Fully proportional hydraulic			

Due to a policy of continuing development and improvement, Niftylift reserves the right to change any specification without notice. Please confirm exact specification before ordering.

\*Weights may vary according to specification / power options, please confirm before ordering.

Supplied by:

**Manufacturers of trailer mounted, self propelled and vehicle mounted platforms.**

**NIFTYLIFT INC**

825 North Driveway,  
Glen Ellyn IL, 60137-5726, USA  
Tel.: 1-800-NIFTYLIFT  
Tel.: 1-630-858-0822  
Fax.: 1-630-858-0520

**NIFTYLIFT LTD**

Fingle Drive, Stonebridge  
Milton Keynes, MK13 0ER  
England, United Kingdom  
Tel.: +44 (0)1908 223456  
Fax.: +44 (0)1908 312733

e.mail: [alastair@niftyliftusa.com](mailto:alastair@niftyliftusa.com) [www.niftylift.com](http://www.niftylift.com) e.mail: [info@niftylift.com](mailto:info@niftylift.com)